

PRODUCT SPECIFICATIONS | opTrilyzer®

QUANTIFICATION OF LATERAL FLOW ASSAYS BASED ON COLOR CHANGE



<i>Application:</i>	intensity quantification of 2 Lines (control/ test; more than 2 lines on request)
<i>User:</i>	professional staff, mobile and clinical usage
<i>Dimensions:</i>	210 mm x 130 mm x 50/ 70 mm (L x W x H)
<i>Dimensions Test Cartridge:</i>	max. 95 mm x 50 mm x 7 mm (L x W x H)
<i>Weight:</i>	ca. 800 g
<i>Display:</i>	4.3" TFT graphic display
<i>Keypad:</i>	10 numeric keys, 5 function keys
<i>Measuring Time:</i>	approx. 15 sec/ measurement
<i>Calibration Card:</i>	SD-card
<i>Memory:</i>	integrated flash-ROM
<i>Memory Capacity:</i>	>1000 patient data files
<i>Interface:</i>	USB port D-sub socket (for printer) SD-card slot
<i>Battery Life:</i>	8 hours
<i>Language Options:</i>	German, English, Spanish, French, Italian
<i>Timer Function:</i>	adjustable upon calibration; factory setting 15 minutes
<i>Barcode Reader:</i>	integrated (barcode label on test cartridge backside)
<i>Operation Temperature:</i>	10°C ... 35°C
<i>Operation Humidity (rel.):</i>	20 ... 85 %
<i>Storage Temperature:</i>	-30°C ... 80°C
<i>Degree of Protection:</i>	IP 20
<i>Power Supply:</i>	lithium ion battery (rechargeable) or AC/ DC converter 100-240 V; 47-53 Hz
<i>External Thermal Printer:</i>	optional
<i>Package Contents:</i>	case with accessories

opTricon GmbH

Schwarzschildstr. 1

12489 Berlin - Germany

fon +49 (0)30. 639 220 35

fax +49 (0)30 .639 220 37

www.optricon.de | info@optricon.de